



CONCRETE TEXTURING TOOL & SUPPLY

45 UNDERWOOD ROAD
1-888-824-2383

THROOP, PA 18512
Fax 1-888-824-2353

www.concrete-texturing.com

REGAL GLOSS

Non-Yellowing Pure Acrylic - VOC Compliant

DESCRIPTION:

Regal Gloss is a non-yellowing pure Acrylic Concrete Sealer designed for decorative concrete such as stamped, overlays, acid stained and exposed aggregate surfaces, as well as brushed or trowel finished concrete surfaces.

Regal Gloss brings out the beauty of decorative and aggregate driveways, patios and sidewalks as well as any concrete surface where protection or sealing is needed.

Regal Gloss offers improved resistance to rain, sun, freezing temperatures, stains, and other pollutants. Applying **Regal Gloss** to exposed aggregate will also help eliminate loose pebbles and premature wear. **Regal Gloss** is formulated with highly durable 100% acrylic resins with substrate wetting agents and anti-foaming additives to help ensure excellent adhesion and eliminate bubbles for extended life of the coating.

TECHNICAL DATA:

Solids..... 25%
Finish..... High Gloss
Coverage (Aggregate)..... 100-125 sq ft/Gallon
Coverage (Decorative, Trowel Finished)..... 200-300 sq ft/Gallon
Drying Time (to touch)..... 30 min -1 hour
Drying Time (traffic)..... 12 - 15 hours
Application Temperature..... Above 40 Degrees F
VOC......349 grams/liter

RESTRICTIONS AND PRECAUTIONS:

- Regal Gloss** should always be tested on a small sample area on the exact same surface prior to the actual application to check for material compatibility, adhesion, and desired physical appearance, and only applied to fully cured concrete (28 day old).
 - **Regal Gloss** should not be applied when air and concrete temperatures are between 40F-85 degrees F.
 - **Regal Gloss** should not be the subject of excessive foot or automobile traffic until it has had sufficient time to dry completely. The dry time will differ based on the weather, temperature, and humidity. Please note that sealing in high temperatures and humidity can cause bubbling, accelerated drying, and entrapped solvent.
 - **Regal Gloss** should always be applied at only the recommended coverage rates and never beyond. Thick applications will increase the risk of sealer malfunction.
- Regal Gloss** should never be applied to any surface intended to receive other coatings besides **Regal Gloss**. A second coat of **Regal Gloss** is recommended when needed but only where a heavy film is not present. A very heavy film of built up sealer should not be sealed over.
- **Regal Gloss** can never be applied when any moisture, morning dew, frost or precipitation is present. It is always recommended that a full 24 hour time frame be used after time of rinse, rain, etc.

PACKAGING:

Regal Gloss is available in 55-gallon drums & 5-gallon pails.

SPECIFICATIONS:

ASTM-C 309, Type 1, Class A
AASHTO-M-148, Type 1, Class B
ASTM C-1315 Type 1, Class A
DRIED COATING IS USDA ACCEPTED